



## Face

**Product:** Matt Coated woodfree paper with a green fluorescent coating

**Use:** Eye-catching labels for pricing, display, promotions & warning signs

**Typical Face  
Values:**

**Substance:** 80 gsm +/- 5

**Caliper:** 82µm +/- 5

**Printability:** Suitable for printing on flexo (all types), letterpress (conventional & UV), thermal transfer, laser, screen printing & hot stamping

## Adhesive

**Type:** General use acrylic permanent adhesive

**Composition:** Aqueous compounded acrylic emulsion

**Use:** For smooth & slightly rough or curved surfaces.

**Typical Adhesive  
Values:**

**Minimum application temperature:** +5°C

**Minimum service temperature:** -20°C

**Maximum service temperature:** +80°C

## Release Liner

**Backing:** HG65

**Product:** Super calendered translucent glassine paper

**Use:** Designed for automatic labelling applications & photocell dispensing systems.  
The liner provides good tear resistance & smooth and regular thickness.

**Typical Release  
Liner Values:**

**Substance:** 62 gsm

**Caliper:** 52µm

Unit 9  
Lancaster Road  
Carnaby Industrial Estate  
Carnaby  
Bridlington  
East Yorkshire  
YO15 3QY

**Tel.** +44 (0)1262 602222

**Fax.** +44 (0)1262 677007

**Email.** sales@greenstik.co.uk