

Specification Sheet

Fluorescent Red Permanent HG65



CONVERTING WITH A DIFFERENCE

Face

Product: Matt Coated woodfree paper with a red fluorescent coating

Use: Eye-catching labels for pricing, display, promotions & warning signs

**Typical Face
Values:**

Substance: 80 gsm +/- 5

Caliper: 82µm +/- 5

Printability: Suitable for printing on flexo (all types), letterpress (conventional & UV), thermal transfer, laser, screen printing & hot stamping

Adhesive

Type: General use acrylic permanent adhesive

Composition: Aqueous compounded acrylic emulsion

Use: For smooth & slightly rough or curved surfaces.

**Typical Adhesive
Values:**

Minimum application temperature: +5°C

Minimum service temperature: -20°C

Maximum service temperature: +80°C

Release Liner

Backing: HG65

Product: Super calendered translucent glassine paper

Use: Designed for automatic labelling applications & photocell dispensing systems.
The liner provides good tear resistance & smooth and regular thickness.

**Typical Release
Liner Values:**

Substance: 62 gsm

Caliper: 52µm

Unit 9
Lancaster Road
Carnaby Industrial Estate
Carnaby
Bridlington
East Yorkshire
YO15 3QY

Tel. +44 (0)1262 602222

Fax. +44 (0)1262 677007

Email. sales@greenstik.co.uk