

### Face

**Product:** White glossy biaxially-orientated polypropylene film with print-receptive top coating. Good temperature and chemicals resistance. Good moisture barrier properties

**Use:** High quality labeling of cosmetics & toiletries where durability and resistance to moisture and chemicals are required. Also recommended for the labelling of fruit & vegetables

#### Typical Face

**Values:** **Substance:** 58gsm +/- 5  
**Caliper:** 60µm +/- 5

**Printability:** Suitable for printing on flexo solvent-base, UV flexo, flexo water-based, letterpress (conventional & UV), conventional offset, screen printing & hot stamping

### Adhesive

**Type:** General use acrylic permanent adhesive

**Composition:** Aqueous compounded acrylic emulsion

**Use:** For smooth & slightly rough or curved surfaces.

#### Typical Adhesive

**Values:** **Minimum application temperature:** +5°C  
**Minimum service temperature:** -20°C  
**Maximum service temperature:** +80°C

### Release Liner

**Backing:** WG65

**Product:** Super calendered white translucent glassine paper

**Use:** Designed for automatic labelling applications & photocell dispensing systems. The liner provides good tear resistance & smooth and regular thickness.

#### Typical Release

**Liner Values:** **Substance:** 62gsm  
**Caliper:** 52µm

Unit 9  
Lancaster Road  
Carnaby Industrial Estate  
Carnaby  
Bridlington  
East Yorkshire  
YO15 3QY

**Tel.** +44 (0)1262 602222

**Fax.** +44 (0)1262 677007

**Email.** sales@greenstik.co.uk