## Specification Sheet

## Semigloss Permanent HG65



## Face

**Product:** White wood-free machine coated semi-gloss paper.

**Use:** Universal label paper for multicolour labels requiring high contrast and fine

printing detail.

**Typical Face** 

**Values:** Substance: 80 gsm

Caliper: 70 µm

**Printability:** Flexography, letterpress, offset, rotogravure, hot foil and screen. Suitable for

thermal transfer printing with wax/resin ribbons.

Adhesive

**Type:** General purpose strong permanent.

**Composition:** Acrylic.

**Use:** Good adhesion to all normal substrates, including non-polar surfaces, films

and corrugated board. Good low temperature performance.

**Typical Adhesive** 

**Values:** Minimum application temperature: 0°C

**Minimum service temperature:** -20°C **Maximum service temperature:** 80°C

Release Liner

**Backing:** HG65

**Product:** Yellow transparent glassine backing paper.

**Use:** Backing paper for all reelstock applications. Suitable for automatic dispensing.

**Typical Release** 

**Liner Values:** Substance: 60 gsm

Caliper: 53 µm

Unit 9 Lancaster Road Carnaby Industrial Estate Carnaby Bridlington East Yorkshire YO15 3QY

Tel. +44 (0)1262 602222 Fax. +44 (0)1262 677007 Email. sales@greenstik.co.uk





